

Designed for safety. Built for fun.

UltraScreen Specifications

COLORS



Material: High Density Knitted Polyethylene

Standard Heights: 3'8" (for 4' chain link) 5'8" (for 6' chain link) 7'8" (for 8' chain link)

Density: 90%

Weight: 5 oz/sq-yd (ASTM-D3776)

Tear Strength: Warp 51lbs/Fill 52lbs (ASTM-D 5587, Opt #1)

Breaking Strength: Warp 107lbs/Fill 125lbs (ASTM-D5034)

Bursting Strength: 202 psi (ASTM-D3786)

Thread: #135 Polyester

Hems: 3-ply reinforced with a polypropylene binding

Grommets: #2 brass grommets every 12" with triple grommets corners

Grommet Strip: **Standard on Hts Over 8'*** #2 brass grommets every 24"

Limited Warranty 4 Years

Constructed with high density polyethylene for excellent outdoor longevity. It is also knitted, so if the material is cut or torn it will not unravel. Available in 3 different finishing options:

- **150' Rolls** – Extra polyethylene yarn is knitted into the top and bottom edges so Ultra 90 is ready to install right off the roll.
- **150' Plus Rolls** – Top and bottom edges are sewn with a double-stitch 3-ply hem and grommets every 12". The ends can be cut on site and folded over for reinforcement.
- **Custom** – All edges are sewn with a double-stitch, 3-ply hem and grommets every 12". Panels are custom cut to your specifications.